



Sonicbloc

Polyester Fiber wall panel for acoustic & thermal insulation, in a variety of colors

Description

Sonicbloc is a 100% polyester fiber, homogeneous wall panel ensuring high sound absorption. Sonicbloc can be applied on any surface irrespective of the finish and is available in a variety of colors. Environment friendly, fire retardant, recyclable and user friendly features makes it an ideal material for interiors.



- 100% recyclable
- Flexible to take shapes
- Dimensional stability
- Fire retardant
- No toxic fumes
- Formaldehyde free
- No skin irritation on contact
- No respiratory problems
- Resilient in nature
- Not affected by humidity

Application Areas

- Auditoriums
- Theatres



- Libraries & Classrooms
- Lounge
- Restaurant & Hotels
- Offices & commercial space
- Meeting & Conference rooms
- Museums & galleries
- Canteens
- Concert Hall etc

Installation

The material should be installed on a smooth, clear and dry walls which should be free from any undulations, using water based adhesive.

Installation With Cavity:

Sonicbloc can be installed on G.I Frame / Grid system with infill of required thickness of rock wool / glass wool to suit the specific requirement





Color Palette

of sound & vibration control along with calcium silicate board or any other substrate to meet the specific acoustical requirements.

Supply

Thickness: 10 mm & 12 mm

Size: 1200 mm x 2400 mm

Weight: 2 kg/sqm



Available in a range of solid colors

Physical Properties

Property	Value	
Material	100 % polyester fibers	
Thickness	10 mm & 12 mm	
Sabin Rating	0.7 : 1 m ² metric Sabin	
NRC (Panel Only)	0.9 – 0.95	500 Hz – 0.85 1000 Hz – 0.87 2000 Hz – 0.93 3000 Hz – 0.95
Fire	Fire Retardant (Self Extinguishing)	
Water absorption	Low	

SRD INFRA

Address:

886, 8th Floor, Aggarwal Millennium Tower-II Netaji Subhash Place, Pitampura Delhi-110034

Contact Us:

Tel: +91 11-40197373 / 47028111

Email: sales@srdinfra.com
Website: www.srdinfra.com